

DESIGN AND
FABRICATION

Materials and processing

All stainless steel welded construction, meeting the highest standards of hygiene and durability. Reduced heat dissipation thanks to profiled gasket, easy to remove for perfect maintenance.

Central Cooling System Connection

Ginox is able to choose, size and regulate all the components. Custom Displays have the perfect temperature control no matter which is the central cooling system to where they are connected: Glycol, CO2, R448, R449, R454, R455, ...

Options

Easy access to the technical unit via a key on the front of the unit.

EQUIPMENT

Tools and features

Optimum air circulation for fast, even cooling. The Upright features a digital controller and display for precise control and easy parameter setting. Adjustable support grids guarantee unique equipment configuration.

R290 refrigerant

Stand-alone COLD range exclusively cooled with R290, the most environmentally-friendly refrigerant on the market. with a low energy consumption thanks to reinforced insulation, innovative design and optimal control.



UP
RIGHT

CERTIFICATIONS, SIGNS OF EXCELLENCE



ACTIVE ASSOCIATIVE PRESENCE



GINOX SA

Route des Châtaigniers 13
1816 Montreux, Switzerland

+41 21 925 49 49
info@ginoxgroup.com

Rue Eugène-Marziano 17
1227 Genève, Switzerland

+41 22 849 83 11
info@ginoxgroup.com

GINOX UAE LLC

Exit 119, Ras al Khaimah
United Arab Emirates

+971 7 244 4567
info@ginoxgroup.com

Ginox reserves the right to change its specifications without notice.

GINOXGROUP.COM



GINOX COLD CABINETS COMBINE SLEEK DESIGN WITH DURABLE TECHNOLOGY



- Service hatch
easy maintenance
- Digital electronic regulator
precise control
- Isolation
CFC-free, high-performance
- Refrigerator R290
ecological
- Locks and door closers
self-closing door with key lock

Stainless steel 1.4301
durable, design, hygienic

Removable grids and supports
modularity

Rounded corners and negativ bottom
ergonomic

Adjustable feet
flexibility

Door seals
ease of maintenance

KNOWHOW | ECOLOGY | DESIGN

100% GINOX EXPERTISE

Swiss Know How: Ginox Swiss Kitchen is an industrial company founded in 1875, active in the manufacturing and supply of innovative, high quality and sustainable food service solutions for commercial kitchens. Manufactured products include hoods and ventilated ceiling with patented and proprietary self-cleaning and filtration technology, cooking suites with modern design, versatile and practical refrigerated displays and a full range of fridges,

cabinets, and furniture in stainless steel conforming to the highest specifications in terms of hygiene, usability, and durability.

From its headquarters in Montreux, Switzerland, to its factory in Ras Al Khaimah, United Arab Emirates, it provides turnkey project solutions and services and delivers standard and custom-made products and appliances to clients and kitchen contractors around the world.



UPRIGHT REFRIGERATOR

Models	One Door	Two Half Doors	Two Doors
Length [mm] (A)	710	710	1'350
Depth [mm]	825	825	825
Height [mm]	2'100	2'100	2'100
Electrical connection	230V / 50Hz	230V / 50Hz	230V / 50Hz
Refrigerant gas	R290	R290	R290
Chiller			
Temperature Range [°C]	-2° / +10°	-2° / +10°	-2° / +10°
Electrical Power [W]*	175 / 219	175 / 219	256 / 300
Cooling Capacity [W]**	342	342	513
Refrigerated Gross Volume [L]	580	580	1'205
Defrosting	Hot gas	Hot gas	Hot gas
Freezer			
Temperature Range [°C]	-20° / -15°	-20° / -15°	-20° / -15°
Electrical Power [W]*	360 / 428	360 / 428	554 / 622
Cooling Capacity [W]**	410	410	584
Refrigerated Gross Volume [L]	580	580	1205
Defrosting	Hot gas	Hot gas	Hot gas

* The electrical power rate of monoblock units [W]: high efficiency / standard
 ** Cooling Capacity at evaporating temperature -10°C and ambient 40°C
 ** Cooling Capacity at evaporating temperature -30°C and ambient 40°C



UPRIGHT